



United Paints Limited
P.O. Box 21 064
29 Empire Road
Bridgend
Christchurch
Telephone : (03) 323 8743
Facsimile : (03) 323 7261

Manufacturers of Industrial & Decorative Coatings

SYNCRO PRIMER

Zinc Chromate Anti-Corrosive Primer

Single pack , high build primer for general industrial , marine and automotive use .

Can be overcoated with a wide range of decorative topcoating systems or left as a protective one coat finish in mild environments such as structural steel .

Fast drying nature allows early recoat or topcoating .

Typical Uses

- Structural Steel
- Bridges
- Tank Exteriors
- Pipework
- Machinery
- Rolling Stock
- Industrial Plants
- General Marine
- Automotive
- Maintenance

Specifications may be updated or revised at times . Please ensure through our representative that sheet being viewed is current .

Physical Properties

Vehicle Type	Phenolic Modified Alkyd
Pigment Type	Zinc Chromate
Solvent	Aliphatic / Aromatic
Pot Life	Not Applicable
Gloss Level	Very Low Sheen
Volume Solids	58 %
Colours Available	Green / Yellow / Red Oxide shades.
Recommended Dry Film Build	50 - 70 microns per coat
Theoretical Coverage	12 m ² /lt @ 50 microns DFT
Number of Coats	One (Double head coat)
Dry Time	Touch 30 min @ 20° C Hard 4 - 5 hrs @ 20° C
Recoating Times	<u>Minimum</u> -Varies with topcoat and application. Generally overnight <u>Maximum</u> -Depending on length of exposure 6 months . Hardening may necessitate sanding / reprime .
Abrasion Resistance	Very good
Solvent & Chemical Resistance	Excellent when topcoated appropriately .
Heat Resistance	Up to 85° C (dry heat)
Durability	Very Good
Thinning & Cleanup	Enamel or Commercial
Pack Sizes	4 Litres & 20 Litres
Surface preparation	Surface must be free from dirt , rust grease or moisture and suitably hand or mechanically abraded .

Performance

Performance	<ul style="list-style-type: none"> • Zinc Chromate Reinforced . • Single Pack • Excellent Interim Durability . • Can be overcoated with acrylics alkyds , vinyls and some urethanes • High Build potential .
Limitations	<ul style="list-style-type: none"> • Spray Application is preferred application for early recoating . • Product is designed for interim outdoor exposure . Up to 6 months exposure expected . When exposure is longer please consult with the manufacturer .