



United Paints Limited

P.O. Box 21 064

29 Empire Road

Bridgend

Christchurch

Telephone : (03) 323 8743

Facsimile : (03) 323 7261

Manufacturers of Industrial & Decorative Coatings

## CONCRETE SEALER

### Solution Acrylic Concrete Sealer

Single pack , fast drying thermoplastic acrylic coating designed with a mid to high Tg to coat and seal concrete paths and driveways with good hot tyre resistance.

### Typical Uses

- Pathways
- Driveways
- Garage Floors
- Ornaments
- Castings

Specifications may be updated or revised at times. Please ensure, through our representative, that sheet being viewed is current .

### Physical Properties

Vehicle Type	Thermoplastic Acrylic
Pigment Type	Clear
Solvent	Aromatic
Pot Life	Not applicable
Gloss Level	Full Gloss Standard
Volume Solids	24 %
Colours Available	Clear
Recommended Dry Film Thickness	25 micron
Theoretical Coverage	6 sq. / m per litre
Number of Coats	One
Dry Time	Touch 10 mins Hard 20 mins
Recoating Times	<u>Minimum</u> -2 - 3 hours <u>Maximum</u> -N/A
Abrasion Resistance	Good
Solvent & Chemical Resistance	Very Good.
Heat Resistance	Very Good
Durability	Excellent
Application	May be applied with roller or brush . Can be sprayed when reduced with suitable solvent .
Thinning & Cleanup	Xylene
Pack Sizes	4 Litres & 20 Litres

### Performance

Performance	<ul style="list-style-type: none"><li>• Protects concrete form staining</li><li>• Single Pack</li><li>• Excellent Adhesion .</li><li>• Can be tinted with oxide pigments or suitable solvent based colourants.</li><li>• Good surface penetration for key.</li></ul>
Limitations	<ul style="list-style-type: none"><li>• Must be applied with absolutely no moisture present.</li><li>• Product is designed for adhesion to concrete .Other substrates will need careful testing eg terracotta</li><li>• Film thickness is difficult to establish as sealing is products ultimate purpose.</li></ul>

Christchurch  
(03) 323 8743

Auckland  
(09) 265 0032

Palmerston North  
021 682 151