

Manufacturers of Industrial & Decorative Coatings

United Paints Limited P.O. Box 21 064 29 Empire Road Bridgend Christchurch Telephone : (03) 323 8743 Facsimile : (03) 323 7261

SAFETY DATA SHEET PSEUDOTHANE THINNER

1.0 Chemical Product and Company Identification

Trade Name:

PSEUDOTHANE THINNER

Chemical Name:

Paint Thinner

17th May 2023

Manufacturers Name: Address: Telephone: Facsimile: United Paints 29 Empire Rd, Belfast, Christchurch (03) 323 8743 (03) 323 7261

Date of Issue:

Emergency Contact Numbers

National Poison & Hazardous Chemicals Information Centre United Paints Limited – Director (Mr M.Davies) (03) 474 0999 (03) 359 3528 Home 021 617 979 Mobile

2.0 Hazards Identification

HSNO APPROVAL CODE : HSR002662

HSNO CLASSIFICATIONS :

3.1B , 6.1D , 6.3A , 6.4A , 6.8B , 6.9B , 9.1B , 9.3C

Warning



3.0

Composition / Information on Ingredients

Ingredien	It
-----------	----

% By Weight

 Solvent naptha light
 20 - 40 %

 PMI Acetate
 20 - 40 %

 N Butyl Acetate
 20 - 40 %

890 mg/m³ 550 mg/m³

 724 mg/m^{3}

TLV (TWA)

300ppm 50ppm 150ppm

Auckland (09) 265 0032

Palmerston North 021 682 151

	4.0 First Aid	Measures
4.1	Inhalation	Bring patient to fresh open air. If breathing difficult give oxygen.
4.2 4.3	Skin Contact Eye Contact	Wash with soap and water. Remove and launder contaminated clothing before reuse. Flush with water lifting lids occasionally. Seek medical attention.
4.4	Ingestion	Do not induce vomiting. Keep patient warm and quiet. Seek medical attention immediately. Rinse mouth with water.
4.5	First Aid Facilities	Eyewash and normal washroom facilities and consumerables .
4.6	Notes to Doctor	Treat symptomatically . Aspiration is the main danger . Enforce bed rest and observe carefully . Prophylactic antibiotics useful . Observe for chemical pneumonitis . Gasto-intestinal absorption is significant with hydrocarbon solvents .For large ingestions cuffed endotracheal tube is recommended .

5.0 Fire Fighting Measures

- 5.1 Flashpoint 27°C
- 5.2 Flammability Limit 0.8 (Lower)

5.3 Extinguishing Media

Foam, carbon dioxide, dry chemical.

5.4 Hazardous Composition Products

May form toxic materials such as Carbon Monoxide and Carbon Dioxide.

5.5 Special Firefighting Procedures

Call Fire Service and tell them of location and nature of hazard . Water or Foam may cause frothing that can be violent, especially if sprayed into containers of hot burning liquid. Self contained breathing apparatus with full face piece should be used.

Closed containers can be kept cool by water spray .

Make sure of adequate supplies of extinguishing material available .

5.6 Unusual fire and Explosion Hazards

Vapours are heavier than air and may travel along ground and move by ventilation and ignite at a point far from the source. Sumps and drains should be checked for signs of accumulation .

5.7 Firefighting Personal Protective Equipment

Full protective clothing and self contained breathing apparatus . Water rinse shower available .

Christchurch (03) 323 8743

Auckland (09) 265 0032

	6.0 Accidental	Release Measures
	6.0 Accidental	Release measures
6.1	Minor Spills	Eliminate all sources of Ignition. Stop leak at source. Dyke area of spillage. Absorb with sand or other absorbent inert material.
6.2	Major Spills	Clear are from all public and personnel . Call fire service and advise on the nature of hazard . Ensure spill is contained however if spill enters waterways directly or through drains advise local environment protection authority .
6.2	Disposal	Destroy by controlled incineration by approved waste disposal group or use an authorised disposal area.
	7.0 Handling a	Ind Storage
7.1	Handling	Use in well ventilated area away from any source of ignition . Wear safety glasses , nitrile gloves , overalls , and approved cartridge respirator when spraying .
7.2	Storage	Store in a cool , authorised room away from any source of accidental ignition , or any oxidising agents .

8.0 Exposure Controls / Personal Protection

8.1 Exposure Controls

Contains > 30 % Aromatic Hydrocarbon solvent . Make sure level maintained below TLV of 50 ppm or provide personal protective equipment to suit .

8.2 Personal Protective Equipment

X	Vapour Respirator
	Splash Goggles

- Face Shield
- Gloves (Nitrile)
- Synthetic Apron
- Vapour Respirator
 - vapour Respirator
- Dust Respirator

9.0 Physical and Chemical Properties

Liquid

126°C

27° C

- 9.1 Appearance
- 9.2 Odour
- 9.3 Boiling Point
- 9.4 Flash Point
- 9.5 Solubility in Water
- 9.6 Specific Gravity
- 9.7 ph Value

Christchurch (03) 323 8743

Negligible 0.92 Not applicable Auckland

(09) 265 0032

Hydrocarbon/Ester

Palmerston North 021 682 151

9.8	Vapour Pressure	60 mm Hg at 20°C
9.9	Vapour Density	3.8
9.10	Evaporation Rate	0.8 (BA=1)
9.11	Volatile Component	100 %
9.12	Flammability	Flammable Liquid
9.13	Autoignition Temp	520°C
9.14	Flammability Limits	Lower 0.8 Upper 7.2

Coloured flammable liquid with a mild solvent odour , which does not mix with water but will form a thin layer on water surface .

10.0 Stability and Reactivity

10.2 10.3	Chemical Stability Conditions to Avoid Materials to Avoid Hazardous Decomp Products	Stable under normal conditions Heat , Direct Sunlight , open flames or other ignition sources Strong oxidising agents Carbon monoxide , Carbon dioxide , fumes
	Hazardous Reactions Hazardous Polymerization	May react with incompatible materials Will not occur

11.0 Toxicological Information

11.1	Acute Toxicity	Oral : Moderately Toxic
		Dermal : Slightly Toxic
		Inhalation : Moderate Irritant

11.2 Health Effects Harmful . Ingestion of this material may irritate the gastric tract and cause nausea and vomiting . Eye Contact May cause eye irritation,stinging,redness and blurred vision. Skin Contact May cause itching,redness and irritation Chronic Effects Prolonged contact with skin may cause dermatitis .

12.0 Ecological Information

- **12.1 Ecotoxicity** No ecological data is available for this product .
- 12.2 Persistance / Not readily biodegradable . Degradability

12.3 Mobility AirSlow loss by evaporationWaterProduct will mix partially with water .

12.4 Enviro Protection Avoid contaminating waterways , soil , drains and sewers .

13.0 Disposal Considerations

- **13.1 Liquid** Dispose of waste through an approved facility .
- **13.2 Containers**Dispose of containers through metal recycler once empty
containers have dried .

14.0 Transport Regulations

Labelling Required	FLAMMABLE LIQUID Red Diamond 3
UNDG	
U N Number	1993
Proper Shipping Name	Hazardous Substance n.o.s
D G Class	3
Hazchem Code	3 Y
Packing Group	III
IMDG (Maritime)	
IMDG Class	3
UN Number	1993
EMS Number	F-E , S-E
IMDG Subrisk	None
Packing Group	III
Special Provisions	163 223 944 955
Marine Pollutant	Not Determined

This material is classified as a class 3 – Flammable Liquid according to NZS 5433 : 1999 Transport of Dangerous Goods on Land .

This material must not be loaded in the same freight container or the same vehicle with :

Class 1	Exposives
Class 2.1	Flammable Gases
Class 2.3	Toxic Gases
Class 4.2	Spontaneously Combustible Substances
Class 5.1	Oxidising substances
Class 5.2	Organic Peroxides
Class 7	Radioactive materials unless specifically exempted

Must not be loaded in the same freight container , but can be in the same vehicle if separated hotizontally by a distance of 3 metes :

Class 4.3 Dangerous when wet substances .

Goods of packing group II or III may be loaded in the freight container or the same vehicle if transported in segregation devices with :

Class 4.2	Spontaneously Combustible Substances
Class 4.3	Dangerous when wet substances
Class 5.1	Oxidising substances
Class 5.2	Organic Peroxides

15.0 Regulatory Information

LabellingClass 3 , Flammable Liquid

Poisons Schedule S 4

Hazard Category Harmful

16.0 Other Information

Revision Date 17th May 2028

NZ Emergency Services Telephone 111

NZ Poison Information Telephone 0800 POISON (0800 764 766)

The above information concerns only the above mentioned product and is not valid with any other product(s). The information is provided to the best of our knowledge, correctly and completely, in good faith but without warranty. It remains the user's responsibility to ensure the information is appropriate for their application of the product.